



SPEAKER _____

SUBJECT _____

DATE _____

MC68000

TOD

- dp not supported!
- Metering code
- VAX Block Driver Skeleton h.p.c? t.m.c?

- Minor devs
Major = BLK/CHAR
BP flags ↑?

DRIVE #
P/L

Read-after-write verify?
EJECT ON CLOSE

E W W C D D V

WAIT FOR
DISK INSERT
IN OPEN

check
Density

00 = 800K
01 = 400K
10 = 720K
11 = 1440K

1dev/dsk/cNdφsφ
d1

N = 9 400K GCR
8 800K GCR
10 720K MFM
11 1440K MFM

2-digit "N" is base

c8dφsφ = 800K GCR ?

OL: c8dφsX

X = 0 800K
1 400K
2 720K
3 1440K

I PREFER THIS

- Installation code for testing; Built-in for release

- Memo on drive numbering & options
JK, ~~PHIL~~, DWB, PHIL, RON, VLB

- ~~GINSU METD PM YHUVS 1800~~

- Maybe do 250 ms timer? (16 ticks)

Yes. Pd.h timeouts
and selfdisk.c.

- Task TILFOUT

T.DISKWAIT
to INSERT?

- Busy wakeups!

~~T.BUSY wakeup~~